



### INDIVIDUAL SECTIONS

Section	Top OD (mm)	Base OD (mm)	Length (mm)
C1B	75	120	3600
C2B	75	145	5600
C3B	134	185	4050
C4B	109	158	3850
C6PB	109	158	3850
C7PB	109	173	5050
C8PB	134	188	4250
C10PB	146	210	5050
C12PB	173	240	5300

### WHOLE SYSTEMS

Mount Height (m)	Sections	Plant Depth (mm)	"E" (mm)	"D" (mm)
6.0	C1B+C6PB	1200	575	305
7.0	C1B+C7PB	1400	575	305
8.0	C2B+C8PB	1600	575	305
10.0	C1B+C4B+C10PB	2000	575	450
12.0	C2B+C3B+C12PB	2400	575	450

### Notes

1. Poles to comply with the following standards: NZS 3404:1997; AS 4100:1998 and NZS 4203.
2. Hot dipped galvanised coating on poles to conform to AS/NZS 4680:1999.
3. Thickness of poles to be 3mm minimum.
4. Poles to be indelibly marked showing manufacturer's identity.

**MANARC**

MANUKAU CITY APPROVED  
REQUIREMENT

DETAIL:

**STEELGAL ROUND TAPERED POLES**

UPDATED:

**APR 2003**

DETAIL No.:

**MR-19**

**MANUKAU CITY COUNCIL**